

## Specifications

<b>Model</b>	IBOX-D525
<b>Processor</b>	Adopt Intel Atom dual core D525 (45nm, 1.8GHz, 1MB second Cache)
<b>Chipset</b>	Adopt Intel NM10 express chipset
<b>RAM</b>	2G DDR3
<b>Display port</b>	Integrated Intel GMA3150 Graphic card Support 1*VGA, 1*HDMI, 1*LVDS display input
<b>Expansion port</b>	2*Mini-PCIE, support WIFI
<b>Storage</b>	1* MINISATA, 2*SATA
<b>Audio</b>	Integrated Realtek ALC662 6 sound channel Support MIC Line-out
<b>Network</b>	1* Intel RTL8111E 1000M Lan, support wake on lan
<b>Back I/O</b>	1* RS232 COM 1* 12V DC_JACK input 1*HDMI 1*VGA 6*USB2.0 1* RJ-45 LAN 1* Mic ,1*Audio
<b>Built-in I/O</b>	2* PWROUT 1* AUDIO pin header 1* LVDS and LVDS INVERTER 1* CPUFAN and SYSFAN 1* FP1 (2*5pin) 1*4pin ATX_12V
<b>BIOS</b>	16MB SMT Flash ROM
<b>WDT</b>	Support hardware reset (256 level, 0~255 sec)
<b>Power supply</b>	DC-12V
<b>Temp</b>	-20°C~60°C
<b>Humidity</b>	0~95% relative humidity, non-condensing
<b>Dimension</b>	234*204*54mm(L*W*H)

