

## Specifications

<b>Model</b>	IBOX-1037UB
<b>Processor</b>	Adopt Intel Celeron dual core 1037U (22nm, 1.8GHz, 2MB second Cache)
<b>Chipset</b>	Adopt Intel NM70 express chipset
<b>RAM</b>	2G DDR3(can up to 8G)
<b>Display port</b>	Integrated Intel HD Graphic card 2500, Support 2*VGA, HDMI LVDS display input
<b>Expansion port</b>	2*MINI-PCIE, support wifi/3G
<b>Storage</b>	1* MINISATA, 3*SATA
<b>Audio</b>	Integrated Realtek ALC662 6 sound channel
<b>Network</b>	2* Intel RTL8111E 1000M Lan, support wake on lan
<b>Back I/O</b>	1 ~ 10 COM optional 1* 12V DC_JACK input 1*HDMI 2*VGA 2* RJ-45 LAN 6*USB2.0 1* Mic , 1*Audio
<b>Built-in I/O</b>	2* PWROUT 1* AUDIO pin header 1* LVDS and LVDS INVERTER 1* CPUFAN and SYSFAN 4*USB2.0 1*GPIO 1* SIM
<b>BIOS</b>	AMI 32M BIOS, ACPI supported, support electricity boot
<b>WDT</b>	Support hardware reset (256 level, 0~255 sec)
<b>Power supply</b>	DC-12V
<b>Temp</b>	-20℃~80℃
<b>Humidity</b>	0~95% relative humidity, non-condensing
<b>Dimension</b>	234*200*65mm(L*W*H)

