



CCE Industrial All In One Panel Touch PC(N2600)

Display Specifications

| LCD SIZE | Resolution | Brightness(upgradable) | Contrast Ratio | Aspect ratio | Viewing Angle (H-V) | Backlight MTBF |
|----------|------------|------------------------|----------------|--------------|---------------------|-------------------|
| 8" | 800*600 | 250nits | 500:1 | 4:3 | 140:120 | LED/40,000 hours |
| 10" | 1024*768 | 250nits | 600:1 | 4:3 | 150:130 | LED/40,000 hours |
| 10.4" | 1024*768 | 400nits | 1200:1 | 4:3 | 160:160 | CCFL/30,000 hours |
| 12.1" | 1024*768 | 500nits | 700:1 | 4:3 | 160:160 | LED/30,000 hours |
| 15" | 1024*768 | 250nits | 500:1 | 4:3 | 160:160 | LED/40,000 hours |
| 17" | 1280*1024 | 250nits | 800:1 | 4:3 | 160:160 | LED/40,000 hours |
| 19" | 1440*900 | 250nits | 1000:1 | 16:10 | 150:150 | LED/40,000 hours |
| 21.5" | 1920*1080 | 250nits | 1000:1 | 16:10 | 150:150 | LED/40,000 hours |

Other Information

| | |
|--------------------------------|---|
| CPU | Intel® Atom™ process N2600 dual core 1.6GHz CPU |
| Chipset | Intel NM10 |
| RAM | 2G 400MHz or 533MHz DDRII SODIMM (4GB Max.) |
| Hard Drive | 32GByte S-ATA SSD Hard Drive(upgradable) |
| Audio | Realtek ALC662, 5.1 Channel High Definition Audio Codec 2x 2W loudspeaker |
| Network | Realtek RTL 8111E, 2x10/100/1000Mbit RJ45 Ports 1 x VGA(standard 15Pin) 4 x USB 2.0 or USB 3.0 2 x RJ-45 for Giga LAN 2 x RS-232 COM Port |
| I/O Ports | 1 x HDMI 1 x Power Switch(screwable) 1 x Earjack 1 x Audio Port 1 x WIFI antenna |
| Touch Screen | Resistive Type 5-Wire |
| Touch Life(contacts) | >50,000,000 times |
| Response time touch-panel (ms) | < 10 |
| Surface hardness | 3H |
| Input force (g) | 20 ~ 150 |
| Mounting | Panel, Wall, Rack, Stand and Arm VESA 100mm x 100mm |
| Operating Temperature (°C) | 0°C ~60°C |
| Storage Temperature (°C) | -15°C ~ 70°C |
| IP Level(front panel) | IP54 |
| Safety | CE / FCC/ROHS |
| Power Adapter | Input: 100VAC~240VAC, 50/60Hz |
| Power Requirement | Output: 12VDC |
| Power Consumption | 12VDC 32W |

3G&GPS module Information(optional)

Module: SIM 5218E: Tri-Band UMTS/HSPA 900/1900/2100MHz
 Video Call with camera sensor Interface;
 WCDMA Diversity;
 HSDPA 7.2Mbps; HSUPA 5.76Mbps
 GRPS multi-slot class 12; EDGE multi-slot class 12;
 UMTS 850/1900/2100: 0.25W
 Output Power: GSM850 /GSM900: 2W;
 DCS1800/PCS1900: 1W;
 Control via AT commands;

Operation temperature: -20 to 70 centigrade;

Ordering Information

| Part No. | Description |
|----------------------|--|
| CCEPC**-N2600/2G-32G | **" 250 cd/m ² (upgradable), XGA fanless panel PC with Intel® Atom™ N2600 dual core 1.6GHz, 802.11b/g/n wireless module, touch screen, 2GB DDR2, SSD32G |

Packing List

| | |
|-------------------------------|---------------------------|
| 4 * Screws Pack | 1 * AC-DC Power Adapter |
| 1 * Touch PC | 1 * User's Manual CD ROM |
| 1 * Touch Pen | 1 * WIFI antenna |
| 1* Srewable Power Plug(3 Pin) | 1 * GPS antenna(optional) |
| 1 * 3G antenna(optional) | 1 * GPS antenna(optional) |

USING TECHNOLOGY TO ENHANCE YOUR CUSTOMER'S EXPERIENCE

mobilatorTM.pl