

## BiBOX-215PC1 (i3-10110U)



BiBOX-215PC1 (i3-10th) v.2 - Metal industrial panel with a powerful Intel Core i3 processor, WiFi and Bluetooth module and extended SSD

<b>Category:</b>	Industrial Panel PC Computers
<b>Manufacturer:</b>	Mobilator
<b>Screen size:</b>	21.5 inch
<b>Resolution:</b>	1920x1080
<b>Aspect ratio:</b>	16:9
<b>Touchscreen:</b>	10 Points Projected Capacitive Touch Screen
<b>Chipset:</b>	Intel
<b>CPU Support:</b>	Intel i3/i7
<b>Installed CPU:</b>	Intel Core i3 10110U
<b>Memory Support:</b>	DDR4
<b>Installed Memory:</b>	4GB
<b>Graphic Card:</b>	Integrated graphics Intel HD Graphics
<b>Audio:</b>	Yes
<b>Storage (HDD) Support:</b>	SSD / HDD
<b>Installed Storage (HDD):</b>	128GB SSD
<b>CD/DVD Drive:</b>	No
<b>LAN:</b>	1xRealtek RTL 8111E Gigabit Ethernet

<b>Wireless LAN card:</b>	Yes
<b>Bluetooth:</b>	Yes
<b>3G:</b>	-----
<b>4G LTE:</b>	Option
<b>GPS:</b>	No
<b>TV Tuner:</b>	No
<b>Watch Dog Timer:</b>	-----
<b>Ports - front panel:</b>	-----
<b>Ports - rear panel:</b>	HDMI VGA 2x USB 3.0 2x USB 2.0 1xLAN Audio 2x RS232 DC-12V
<b>Ports - left panel:</b>	-----
<b>Ports - right panel:</b>	-----
<b>Power:</b>	DC-12V
<b>Supported OS:</b>	Windows 7/8/10, Linux, Ubuntu
<b>Installed OS:</b>	No
<b>Dimensions:</b>	552 x 339 x 57 mm
<b>Weight:</b>	7.5kg
<b>Expansion:</b>	-----
<b>Fanless:</b>	Opcja
<b>Humidity:</b>	5% - 95% Non-Condensing
<b>Temp:</b>	-10 °C to 60 °C
<b>Storage Temp:</b>	-20 °C to 70 °C
<b>IP Norm:</b>	-----
<b>IP Level (back panel):</b>	-----
<b>IP Level (front panel):</b>	IP65
<b>Dual display:</b>	Yes
<b>Response time touch-panel (ms):</b>	----
<b>Contrast Ratio:</b>	800:1
<b>Brightness:</b>	250 cd/m2

<b>Viewing Angle:</b>	89/89/89/89(L/R/U/D)
<b>Backlight MTBF:</b>	-----
<b>Color Resolution:</b>	-----
<b>Surface hardness (display):</b>	-----
<b>Touch Life(contacts):</b>	-----
<b>Housing material:</b>	Aluminium
<b>Mounting VESA:</b>	-----
<b>Folding Bracket (for office type working):</b>	-----
<b>Power Consumption:</b>	-----
<b>Others:</b>	Color: Black
<b>Anti-vibration:</b>	----
<b>Anti-shock:</b>	----
<b>RFID scanner (reader):</b>	No
<b>Barcode reader:</b>	No

**3 932,06 zł**

net price: 3 196,80 zł

# BiBOX-215PC1 (i3-10110U)



## SPECIFICATION AND PARAMETERS

## DISPLAY AND TOUCH

## RESISTANCE AND PROTECTION

## COMMUNICATION AND CONNECTORS

## APPLICATION

## AVAILABLE VERSIONS AND ACCESSORIES

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



#### Efficient cooling

The housing with notches used in the panel ensures good air exchange inside the device



#### Efficient

The quad-core Intel Core i3 10110U improves the device's performance.



#### Wireless network

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module or 4G \*.



#### Quick start

A modern SSD drive will increase the speed of applications and programs and ensure quiet computer operation.



#### Bright Screen

The display with 250 cd/ m<sup>2</sup> brightness makes the picture much more vivid and better readable when used outside in the sun.



#### Capacitive screen

The capacitive screen allows precise handling and gentle on-screen movement.

\* Optional equipment, available only in specific versions of the device.

## Specifications and parameters

## Performance

Processor	Intel Core i3 10110U
Graphics card	Integrated Intel HD Graphics
Operating system	Support for Windows 7/8/10, Linux, Ubuntu
RAM	4GB DDR4
Drive	128GB SSD
<b>Display</b>	
Screen	21.5" 1920x1080
Touch screen	10 Points Projected Capacitive Touch Screen
Brightness	250cd/m <sup>2</sup>
Screen ratio	16:9
View angle	89/89/89/89(L/R/U/D)
<b>Interfaces</b>	
Communication	4G *   WiFi   Bluetooth 4.0
Connectors	2x USB 3.0   4x USB 2.0   2x COM   1x LAN 1x VGA   1x HDMI   DC 12V   1x Audio   1x Mic
<b>Other</b>	
Dimensions	552 x 339 x 57 mm
Weight	7.5 kg
Casing material	Aluminium

\* Optional equipment, available only in specific versions of the device.



Detailed device specification is available in the "Technical data".

The industrial PC panel uses an efficient and energy-saving Intel Core i3 10110U. In its interior there are four cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery".

## Display and touch

Amplified, metal industrial computer BiBOX-215PC1 has a water-resistant and scratch-proof 21.5" LED screen 1920x1080 resolution offers good image quality, and high brightness in the 250 cd/m<sup>2</sup> range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident. The display of the resistive type provides the user with a clear image and ease of use by touch.

## CAPACITIVE SCREEN

The capacitive screen consists of a glass coating that is covered with an insulator. Touching the surface of the touch pad with your finger causes a disturbance in the flow of electric current. This display provides very good visibility under industrial conditions. The panel can be operated with one finger or conductive material (special glove). This type of screen provides support for multi-touch technology, which is a clear convenience during work. This is due to the fact that a large number of electrodes allows accurate detection of many points of touch. You do not have to use a stronger pressure for capacitive screens, because you only need to lightly brush the screen with your finger to make the device react.



Resistance and protection

## QUALITY OF MATERIALS

The panel PC has a good-quality metal casing. It is an important element of the cooling system thanks to specially designed cutouts that facilitate air circulation inside the housing. The overall design of the device is focused on simplicity and functionality, appreciated among professionals, as an accessory the panel can be equipped with passive cooling.



## EXTREME TEMPERATURES

PanelPC BiBOX-215PC1 is designed for continuous operation both at very low and high temperatures in the range from -10 ° C to 60 ° C. If the device is turned off, it can handle temperatures ranging from -20 ° C to 70 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 95% relative air humidity. It is also possible to purchase additional fanless cooling.

Work temp.	-10°C do 60°C
Storage temp.	-20°C do 70°C

Humidity

5% - 95% Non-Condensing

## Communication and connectors

### WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel BiBOX-215-PC1 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

Standards

802.11a/b/g/n

Frequencies

2.4GHz



### 4G MODULE (OPTION)

4G technology is based on a radio network with fast transmission and the rare occurrence of downtime or transfer errors. The main distinguishing feature of

the 4G from its predecessor (3G) is the speed of transfer between devices. The fourth generation network offers 100 Mb / s of mobile internet speed and 25 Mb / s of packet transfer.




## BLUETOOTH COMMUNICATION


Bluetooth enables short-range wireless communication between various electronic devices, such as keyboard computer, laptop, PDA, mobile phone and many others. In the fourth version of standard, energy consumption was significantly reduced transfer and the real range of operation was increased



## CONNECTORS AND INTERFACES



## DIMENSIONS



## TRADE AND SERVICES

PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

## WAREHOUSE AND MANAGEMENT



The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

## TRANSPORT AND MOTORIZATION



Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

### Available versions and accessories

Industrial Panel PC BiBOX-215PC1 is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

	v.1	v.2	v.3	v.4	v.5	v.6	v.7	v.8
4GB RAM			—	—	—	—	—	—
8GB RAM	—	—				—	—	—
16GB RAM	—	—	—	—	—		—	—
64GB SSD	—	—	—	—	—	—	—	—
128GB SSD	—		—	—	—	—	—	—
256GB SSD	—	—			—	—	—	—
512GB SSD	—	—	—	—			—	—
WiFi	—			—	—			

Bluetooth	—	—	—	—	—	—	—
4G	—	—	—	—	—	—	—
Licence Windows 10 PRO	—	—	—	—	—	—	—