



## Efficient industrial PC panel fan-cooled IBOX ITPC A-150 v.3

|                                 |                               |
|---------------------------------|-------------------------------|
| <b>Category:</b>                | Industrial Panel PC Computers |
| <b>Manufacturer:</b>            | Mobilator                     |
| <b>Screen size:</b>             | 15"                           |
| <b>Resolution:</b>              | 1024 x 768                    |
| <b>Aspect ratio:</b>            | -----                         |
| <b>Touchscreen:</b>             | Resistive                     |
| <b>Chipset:</b>                 | Intel i5                      |
| <b>CPU Support:</b>             | Intel i5 4200U (2x 1.6GHz)    |
| <b>Installed CPU:</b>           | Intel i5 4200U (2x 1.6GHz)    |
| <b>Memory Support:</b>          | DDR3L SO-DIMM (max. 8GB)      |
| <b>Installed Memory:</b>        | <b>4GB</b>                    |
| <b>Graphic Card:</b>            | Intel HD Graphics             |
| <b>Audio:</b>                   | -----                         |
| <b>Storage (HDD) Support:</b>   | SSD   HDD                     |
| <b>Installed Storage (HDD):</b> | <b>500GB HDD</b>              |

|                                |                                                                             |
|--------------------------------|-----------------------------------------------------------------------------|
| <b>CD/DVD Drive:</b>           | -----                                                                       |
| <b>LAN:</b>                    | Intel I211AT 10/100/1000 Mb/s                                               |
| <b>Wireless LAN card:</b>      | Intel 6205 Dual-Band 802.11 a/b/g/n                                         |
| <b>Bluetooth:</b>              | No                                                                          |
| <b>3G:</b>                     | No                                                                          |
| <b>GPS:</b>                    | -----                                                                       |
| <b>TV Tuner:</b>               | -----                                                                       |
| <b>Watch Dog Timer:</b>        | -----                                                                       |
| <b>Ports - front panel:</b>    | -----                                                                       |
| <b>Ports - rear panel:</b>     | 2x USB 3.02x USB 2.02x RS2321x Gigabit LAN1x VGA1x HDMI1x Mic1x AudioDC 12V |
| <b>Ports - left panel:</b>     | -----                                                                       |
| <b>Ports - right panel:</b>    | -----                                                                       |
| <b>Power:</b>                  | 12V DC-in                                                                   |
| <b>Supported OS:</b>           | Windows 7/8.1/10   Linux                                                    |
| <b>Installed OS:</b>           | -----                                                                       |
| <b>Dimensions:</b>             | 352mm x 263mm x 45 mm                                                       |
| <b>Weight:</b>                 | 3.0 kg                                                                      |
| <b>Expansion:</b>              | -----                                                                       |
| <b>Fanless:</b>                | Yes                                                                         |
| <b>Humidity:</b>               | 0%~ 95%                                                                     |
| <b>Temp:</b>                   | -10°C ~ 50°C                                                                |
| <b>Storage Temp:</b>           | -20°C ~ 60°C                                                                |
| <b>IP Norm:</b>                | -----                                                                       |
| <b>IP Level (back panel):</b>  | -----                                                                       |
| <b>IP Level (front panel):</b> | -----                                                                       |
| <b>Dual display:</b>           | Yes                                                                         |
| <b>Contrast Ratio:</b>         | 1000:1                                                                      |
| <b>Brightness:</b>             | 350 cd/m2                                                                   |

|                                                   |             |
|---------------------------------------------------|-------------|
| <b>Viewing Angle:</b>                             | Full        |
| <b>Backlight MTBF:</b>                            | LED         |
| <b>Color Resolution:</b>                          | ----        |
| <b>Surface hardness (display):</b>                | ----        |
| <b>Touch Life(contacts):</b>                      | ----        |
| <b>Housing material:</b>                          | Steel       |
| <b>Mounting VESA:</b>                             | Yes         |
| <b>Folding Bracket (for office type working):</b> | ----        |
| <b>Power Consumption:</b>                         | ----        |
| <b>Others:</b>                                    | Color Black |
| <b>Anti-vibration:</b>                            | ----        |
| <b>Anti-shock:</b>                                | ----        |
| <b>RFID scanner (reader):</b>                     | ----        |
| <b>Barcode reader:</b>                            | ----        |

**833,44 €**

net price: 677,59 €



**ITPC**



**A150**



## SPECIFICATION AND PARAMETERS

## DISPLAY AND TOUCH

## RESISTANCE AND PROTECTION

## COMMUNICATION AND CONNECTORS

## APPLICATION

## AVAILABLE VERSIONS AND ACCESSORIES

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



### Active cooling

Use of active cooling in the PC panel ensures stable temperature level and uninterrupted functioning.



### Data storage

Large capacity of hard drive allows storing important user data without need of discarding some of it due to lack of space.



### Efficient

The dual-core Intel i5 4200U processor supported





### Bright Screen

The display with 350 cd/ m<sup>2</sup> brightness makes the picture much more vivid and better readable when used outside in the sun.

by 4 or 8 GB of RAM improves the device's performance.



### Wireless network

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module.



### Resistive screen

The resistive screen allows you to freely use the touch screen of the PC panel in gloves or with a stylus.

## Specifications and parameters

| Performance      |                            |
|------------------|----------------------------|
| Processor        | Intel i5 4200U (2x 1.6GHz) |
| Graphics card    | Intel HD Graphics          |
| Operating system | Windows 7/8/10/CE   Linux  |
| RAM              | 4 GB DDR3L                 |
| Drive            | HDD: 500 GB                |
| Display          |                            |

|                       |                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------|
| Screen                | 15" (1024 x 768)                                                                                    |
| Touch screen          | Resistive, single-point                                                                             |
| Brightness            | 350cd/m <sup>2</sup>                                                                                |
| Screen ratio          | 4:3                                                                                                 |
| View angle            | Full                                                                                                |
| Touch screen lifetime | Over 50 million touches                                                                             |
| Interfaces            |                                                                                                     |
| Communication         | Wi-Fi                                                                                               |
| Connectors            | 2x USB 3.0   2x USB 2.0   2x RS232   1x Gigabit LAN   1x VGA   1x HDMI   1x Mic   1x Audio   DC 12V |
| Other                 |                                                                                                     |
| Dimensions            | 352 x 263 x 45mm                                                                                    |
| Weight                | 3.0 kg                                                                                              |
| Casing material       | Steel                                                                                               |



Detailed device specification is available in the "Technical data" tab.

The dust-proof industrial PC panel uses an efficient and energy-saving Intel i5 4200U processor. In its interior there are two cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery" tab.


## Display and touch

Amplified, waterproof industrial computer ITPC A150 has a water-resistant and scratch-proof 15" LED screen 1024x768 resolution offers good image quality, and high brightness in the 350 cd/m<sup>2</sup> range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident The display of the resistive type provides the user with a clear image and ease of use by touch.

### RESISTIVE SCREEN

In the resistive screen, the sensitive surface is made of two plastic plates. The plate on the surface is made of thin and scratch-resistant plastic. It is also

covered with a thin layer of conductive materials placed on the bottom of the screen. Under the top glass (i.e. below the conductive material) is a second plastic plate. Both tiles have no contact with each other until the user of the device has pressed the screen with a finger or stylus. Then there is contact between slightly separated screens. As a result of their contact, a short-circuit is created, which by measuring the vertical and horizontal resistance is converted into data indicating the processor's contact point.



Resistance and protection

**QUALITY OF MATERIALS**

Panel PC has a high quality casing made from steel alloys. It is a very crucial component of cooling system thanks to openings allowing air flow inside casing, supporting constantly working fan. Overall design concentrates on simplicity and functionality which are in high demand amongst professionals.



## EXTREME TEMPERATURES

PanelPC ITPC A150 is adapted for continuous operation in both very low and high temperatures in the range from -10 ° C to 50 ° C. If the device is switched off, it can already handle temperatures between -20 ° C and 60 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 95% relative humidity.

|               |               |
|---------------|---------------|
| Work temp.    | -10°C do 50°C |
| Storage temp. | -20°C do 60°C |
| Humidity      | 0% - 95%      |

## Communication and connectors

## (OPTIONAL) WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel ITPC A150 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

|             |               |
|-------------|---------------|
| Standards   | 802.11a/b/g/n |
| Frequencies | 2.4GHz   5GHz |

## CONNECTORS AND INTERFACES



## DIMENSIONS



## Application



## TRADE AND SERVICES

PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

## **WAREHOUSE AND MANAGEMENT**

The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

## **TRANSPORT AND MOTORIZATION**

Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

## Available versions and accessories

Industrial industrial computer ITPC A150 is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

|           | v.0 | v.1 | v.2 | v.3 | v.4 | v.5 |
|-----------|-----|-----|-----|-----|-----|-----|
| 4GB RAM   | —   |     |     |     | —   | —   |
| 8GB RAM   | —   | —   | —   | —   |     |     |
| 32GB SSD  | —   |     | —   | —   | —   | —   |
| 64GB SSD  | —   | —   |     | —   | —   | —   |
| 128GB SSD | —   | —   | —   | —   |     | —   |
| 500GB HDD | —   | —   | —   |     | —   | —   |
| 1TB HDD   | —   | —   | —   | —   | —   |     |
| WiFi      | —   | —   |     |     |     |     |