



RS232/422/485



Industrial control panel HMI MK-070AS
IP65 2xCOM Port + Ethernet + SD

Category:	HMI Operator Interface Panels
Manufacturer:	Mobikator
Supported OS:	Linux
Installed OS:	Linux
	: 1x USB 2.0 Host 1x USB 2.0 Slave 2x RS232/422/485
	: Gray
	: ModbusPPIMPI
	: 128MB
	: ARM A8 Core 400MHz
Screen size:	7"
Resolution:	800x480px
Graphic Card:	-----
Brightness:	450cd/m ²
Touchscreen:	4-wire resistive
IP Norm:	IP65 (front panel)
Temp:	0°C - 50°C
Storage Temp:	-20°C - 60°C
LAN:	Yes
Humidity:	10% - 90% non-condensing
Bluetooth:	-----
Others:	-----
Expansion:	-----
Power:	24V

Power Consumption:	6W
Contrast Ratio:	400:1
Color Resolution:	266144
Housing material:	PC/ABS
Dimensions:	203 x 145 x 40mm
Fanless:	Yes
Weight:	~1500g

Product from the Archive - production finished

HMI **MK-070AS** IP65 2xCOM Port + Ethernet + SD



Specification

Description

Available versions

Protection

Communication

Application

Industrial operator panels also known as control panels are devices that control other electrical devices using convenient and intuitive touch interface. Thanks to its robust design, these devices are suitable for use even in harsh environments. Model MK-070BE has a IP65 standard which classifies and rates the degree of protection provided against intrusion (body parts such as hands and fingers), dust, accidental contact, and water by mechanical casings and electrical enclosures.

Specification

Processor	ARM Cortex A8 400MHz
RAM	128MB
Flash memory	128MB
Screen	7" (800x480) TFT
Touchscreen	4-Wire Resistive
Connectors	USB 2.0 (Host) USB 2.0 (Slave) RS232/422/485 RJ-45 LAN SD Card
Operating system	Linux
Communication protocols	Modbus PPI MPI
Dimensions	203mm x 145mm x 40mm
Weight	~1500g
Protection	IP65 (Front panel)

Check "Available versions" tab to see available configurations of this device. To get more information about this product click "Ask about the product" or use the [Contact form](#).



Description



Multitasking OS

HMI is equipped with an operating system from Windows CE family, which ensures maximum efficiency of the device and easily copes with multiple processes simultaneously. Convenient interface makes the operator panels as much intuitive as possible.

Efficient processor

An important advantage of the HMI MK-070BE is a powerful combination of small size with considerable capabilities through the use of the processor family ARM Cortex A8 with 400MHz clock speed, which, combined with 128MB of RAM gives us a powerful, multi-purpose, quality device for a low price.

Small size

HMI MK-070BE is equipped with a 7 inch screen and the overall size of its design is only 203mm x 145mm x 40mm, with cut-out size 192mm x 138mm and its weight is only 1500 grams. With such a small size it can be used in even if there is not much

available space. In addition, HMI has the possibility to mount it on a wall for the greatest convenience and ease of access.

Solid construction

HMI enclosure is made from a specialized blend of PC / ABS (polycarbonate / acrylonitrile-butadiene-styrene) providing a very high resistance to mechanical damage. With this construction it is ready for use even in extreme conditions such as heat, cold or vibration at any time. In addition, the front panel of the device has IP65 international standard, which confirms the water resistance and a complete protection against dust.

Low power consumption








Using the latest technology, HMI MK-070BE is designed for continuous operation with low power consumption of less than 6W at 24V.





Protection

IP65 RESISTANCE

IP stands for Ingress Protection and is essentially a rating system developed by the International Electrotechnical Commission or the IEC. The system is now being used to classify different degrees of protection against intrusion or immersion. The IP rating is usually followed by two digits. The first indicates the level of dust-resistance, the second water resistance. Dust-resistance levels goes from 0 up to 6 while water-resistance goes from 0 to 8.

No protection	0		0	No protection
Protection against any large surface of the body, such as the back of a hand	1		1	Protection against vertically dripping water
Protection from object > 12mm, e.g. Fingers or similar objects	2		2	Protection against vertically dripping water when device is tilted at an angle up to 15 degrees
Protection from object > 2.5mm, e.g. tools, thick wires, etc.	3		3	Protection against direct sprays of water when device is tilted at an angle up to 60 degrees
Protection from object > 1mm, e.g. most wires, slender screws, large ants etc.	4		4	Protection from sprays and splashing of water in all directions
Dust protected - Ingress of dust is almost entirely prevented.	5		5	Protection from low pressure water projected from a nozzle with a 6.3mm diameter opening in any direction
Dust tight - No ingress of dust, complete protection against contact.	6		6	Protection from water projected in powerful jets from a nozzle with a 12.5mm diameter opening in any direction

—	7		7	Protected from immersion in water with a depth of up to 1 meter (or 3.2ft) for up to 30 mins
—	8		8	Protected from immersion in water with a depth of more than 1 meter

Work temperature	0 - 50
Storage temperature	-20 - 60
Humidity	10% - 90% (non-condensing)
Dust resistance	IP6x
Water resistance	IPx5

Available versions



Select a version tailored to your needs. Clicking on the hardware number configurations will redirect you to the product with parameters listed below. At the customer's request can be created configurations which are not available in the offer. Detailed parameters are available in the "Technical Data".

	LAN connector	SD card slot
MK-070AS		
MK-070BE	—	—

Communication



MODBUS

Modbus is a serial communications protocol initially for use with programmable logic controllers (PLCs). Simple and robust, it has since become a standard communication protocol, and it is now a commonly available means of connecting industrial electronic devices. Modbus enables communication among many devices connected to the same network, for example a system that measures temperature and humidity and communicates the results to a computer. Modbus is often used to connect a supervisory computer with a remote terminal unit (RTU) in supervisory control and data acquisition (SCADA) systems.

CONNECTOR TYPE	QUANTITY
USB 2.0 Host	1

USB 2.0 Slave	1
RS232/422/485	1
RJ-45 LAN	1
SD Card	1
DC 24V	1

PLC

PLC is a universal microprocessor device designed to control the operation of the machine or technological equipment. PLC must be adapted to the HMI device by introducing into its memory the desired algorithm for operation of the plant. A characteristic feature of the PLC controller distinguishes this from other drivers computer is cyclic circulation of program memory. The algorithm is stored in a dedicated controller programming language. You can change the algorithm by changing the contents of program memory. The driver provided with a suitable number of input circuits gathering information on the object status and requests service and the appropriate number and type of output devices connected to the actuators, signaling or data.

PLC is not included in the standard equipment - it must be purchased separately.

Application



Industrial HMI operator panel can be used to connect multiple devices in the warehouse and make them easier to control. And its robust design is perfectly designed for the harsh conditions prevailing in these areas. Dust or dirt will not prevent this device from working, it will work flawlessly even in polluted environments.

Thanks to the ease with which it can be adapted to specific tasks, it's widely used for mediation between different processes, giving you control in various situations.

Smart Home

Thanks to its transparent and intuitive touch interface, the HMI device can be easily adapted to the Smart Home, this solution allows you to control functions such as music, heating and air conditioning, from one place. The ideal device for people who like to have everything at your fingertips.

available in the **Technical data** tab.

