



Industrial Operator Panel HMI EX43HA + PLC v.6

| | |
|----------------------|-------------------------------|
| Category: | HMI Operator Interface Panels |
| Manufacturer: | Mobilator |
| Supported OS: | Windows CE 5.0 |
| Installed OS: | Windows CE 5.0 |
| Screen size: | 4.3" |
| Resolution: | 480x272px |
| Brightness: | 300cd/m ² |
| Touchscreen: | 4-wire resistive |
| Processor: | ARM Cortex A9 640MHz |
| Graphic Card: | ----- |
| RAM: | 128MB |
| ROM: | 128MB |
| IP Norm: | IP65 |
| Temp: | -20°C - 60°C |
| Storage Temp: | -20°C - 70°C |
| Humidity: | 20% - 90% |
| Others: | ----- |
| LAN: | Nie |

| | |
|----------------------------------|--|
| Bluetooth: | Nie |
| Connectors: | 1x USB Mini (for HMI programming)1x USB 2.0 |
| Communication protocols: | Mitsubishi PLCModbus |
| PLC: | Yes - Integrated |
| Digital I/O (PLC): | 12/12 |
| Analog I/O (PLC): | Sold separately (see Producer accessories tab), max. 4/2 |
| Output type (PLC): | Relay |
| COM port (PLC): | 1x RS232 |
| Temperature sensor (PLC): | Yes - Thermocouple EK/PT100/NTC10K/50K/100K |
| Expansion: | None |
| Power: | 24V |
| Power Consumption: | Lower than 3W |
| Contrast Ratio: | 400:1 |
| Color Resolution: | 65536 |
| Housing material: | PC/TPU |
| Color: | Grey |
| Dimensions: | 134x102x30mm |
| Fanless: | Yes |
| Weight: | ~400g |

Product from the Archive - production finished



Specification

Description

Available versions

Protection

Communication

Application

Industrial operator panels also known as control panels are devices that control other electrical devices using convenient and intuitive touch interface. Thanks to its robust design, these devices are suitable for use even in harsh environments. Model EX43HA has a IP65 standard which classifies and rates the degree of protection provided against intrusion (body parts such as hands and fingers), dust, accidental contact, and water by mechanical casings and electrical enclosures.

Specification

HMI

| | |
|----------------------|--|
| CPU | ARM Cortex A9 640MHz |
| RAM | 128MB |
| ROM | 128MB |
| Connectors | Mini USB USB 2.0 RS232 (optional) |
| Operating System | Windows CE 5.0 |
| Dimensions | 134x102x30mm |
| Weight | ~400g |
| Protection class | IP65 (front panel) |
| Additional protocols | Modbus Mitsubishi PLC programming protocol |

PLC

| | |
|-----------------------------|------------------------|
| Type | Integrated |
| Max. digital inputs/outputs | 12/12 |
| Min. digital inputs/outputs | 5/5 |
| Output type | Transistor/Relay/Mixed |
| Max. load of transistor | 500mA |
| Max. load of relay | 5A |
| Max. analog inputs/outputs | 4/2 |
| Analog input voltage | 0-10V lub 0-5V |
| Analog input current | 0-20mA lub 4-20mA |
| Analog output voltage | 0-10V lub 0-5V |

| | |
|-----------------------|--|
| Analog output current | 0-20mA |
| Temperature sensor | Thermocouple EK/PT100/NTC10K/50K/100K |
| COM port | 1x RS232 (optionally RS485) |
| Software | Compatible with Mitsubishi GX 8.52 i Works 2 |

Check "Available versions" tab to see available configurations of this device. To get more information about this product click "Ask about the product" or use the [Contact form](#).



Description



Multitasking OS

HMI is equipped with an operating system from Windows CE family, which ensures maximum efficiency of the device and easily copes with multiple processes simultaneously. Convenient interface makes the operator panels as much intuitive as possible.

Efficient processor

An important advantage of the HMI EX43HA is a powerful combination of small size with considerable capabilities through the use of the processor family ARM Cortex A9 with 640MHz clock speed, which, combined with 128MB of RAM gives us a powerful, multi-purpose, quality device for a low price.

Small size

HMI EX43HA is equipped with a 4.3 inch (119mm x 93mm) screen and the overall size of its design is only 134mm x 102mm x 30mm, with a cutout size of 119mm x 93mm and its weight is only 400 grams. With such a small size it can be used in even if there is not much available space. In addition, HMI has the possibility to mount it on a wall for the greatest convenience and ease of access.

Solid construction

HMI enclosure is made from a specialized blend of PC / ABS (polycarbonate / acrylonitrile-butadiene-styrene) providing a very high resistance to mechanical damage. With this construction it is ready for use even in extreme conditions such as heat, cold or vibration at any time. In addition, the front panel of the device has IP65 international standard, which confirms the water resistance and a complete protection against dust.

Low power consumption

Using the latest technology, HMI EX43HA is designed for continuous operation with low power consumption of less than 3W at 24V.

Protection

IP65 RESISTANCE

IP stands for Ingress Protection and is essentially a rating system developed by the International Electrotechnical Commission or the IEC. The system is now being used to classify different degrees of protection against intrusion or immersion. The

IP rating is usually followed by two digits. The first indicates the level of dust-resistance, the second water resistance. Dust-resistance levels goes from 0 up to 6 while water-resistance goes from 0 to 8.

| | | | | |
|--|---|---|---|--|
| No protection | 0 |  | 0 | No protection |
| Protection against any large surface of the body, such as the back of a hand | 1 |  | 1 | Protection against vertically dripping water |
| Protection from object > 12mm, e.g. Fingers or similar objects | 2 |  | 2 | Protection against vertically dripping water when device is tilted at an angle up to 15 degrees |
| Protection from object > 2.5mm, e.g tools, thick wires, etc. | 3 |  | 3 | Protection against direct sprays of water when device is tilted at an angle up to 60 degrees |
| Protection from object > 1mm, e.g. most wires, slender screws, large ants etc. | 4 |  | 4 | Protection from sprays and splashing of water in all directions |
| Dust protected - Ingress of dust is almost entirely prevented. | 5 |  | 5 | Protection from low pressure water projected from a nozzle with a 6.3mm diameter opening in any direction |
| Dust tight - No ingress of dust, complete protection against contact. | 6 |  | 6 | Protection from water projected in powerful jets from a nozzle with a 12.5mm diameter opening in any direction |
| — | 7 |  | 7 | Protected from immersion in water with a depth of up to 1 meter (or 3.2ft) for up to 30 mins |
| — | 8 |  | 8 | Protected from immersion in water with a depth of more than 1 meter |

| | |
|---------------------|----------------------------|
| Work temperature | -20 - 60 |
| Storage temperature | -20 - 70 |
| Humidity | 20% - 90% (non-condensing) |
| Dust resistance | IP6x |
| Water resistance | IPx5 |

Available versions



Select a version tailored to your needs. Clicking on the hardware number configurations will redirect you to the product with parameters listed below. At the customer's request can be created configurations which are not available in the offer. Detailed parameters are available in the "Technical Data".

| | Digital input | Digital output | Analog input | Analog output | RS232 in HMI | Output type |
|------------|---------------|----------------|--------------|---------------|--------------|-------------|
| EX43HA v.1 | 8 | 8 | — | — | — | Transistor |
| EX43HA v.2 | 12 | 12 | — | — | — | Transistor |
| EX43HA v.3 | 12 | 12 | 4 | 2 | — | Transistor |
| EX43HA v.4 | 8 | 8 | — | — | — | Relay |
| EX43HA v.5 | 12 | 8 | — | — | — | Relay |
| EX43HA v.6 | 12 | 12 | — | — | — | Relay |

Communication



MODBUS

Modbus is a serial communications protocol initially for use with programmable logic controllers (PLCs). Simple and robust, it has since become a standard communication protocol, and it is now a commonly available means of connecting industrial electronic devices. Modbus enables communication among many devices connected to the same network, for example a system that measures temperature and humidity and communicates the results to a computer. Modbus is often used to connect a supervisory computer with a remote terminal unit (RTU) in supervisory control and data acquisition (SCADA) systems.

| CONNECTOR TYPE | QUANTITY |
|------------------|----------|
| USB 2.0 | 1 |
| RS232 (optional) | 1 |
| DC 24V | 1 |



Warehouse

Industrial HMI operator panel can be used to connect multiple devices in the warehouse and make them easier to control. And its robust design is perfectly designed for the harsh conditions prevailing in these areas. Dust or dirt will not prevent this device from working, it will work flawlessly even in polluted environments.

available in the **Technical data** tab.

Thanks to the ease with which it can be used for specific tasks, it's widely used in the mediation between different processes, giving you more control in various situations.

