

MOBITOUCH 116A-LF



Mobitouch 116A-LF v.7 - Rugged panel computer (IP65 Front) for warehouse use with resistive touchscreen, NFC, WiFi and 125 kHz RFID reader

Category:	Industrial Panel PC Computers
Manufacturer:	Mobikator
Screen size:	11.6 inch
Resolution:	1366x768
Aspect ratio:	16:9
Touchscreen:	Resistive
Chipset:	AMD
CPU Support:	RK3568
Installed CPU:	RK3568
Memory Support:	DDR4
Installed Memory:	4GB
Graphic Card:	Integrated graphics Intel HD Graphics
Audio:	Yes
Storage (HDD) Support:	eMMC
Installed Storage (HDD):	64GB eMMC

CD/DVD Drive:	No
LAN:	1xRealtek RTL 8111E Gigabit Ethernet
Wireless LAN card:	Yes
Bluetooth:	Yes
3G:	-----
4G LTE:	No
GPS:	No
TV Tuner:	No
Watch Dog Timer:	Option
Ports - front panel:	-----
Ports - rear panel:	Phoenix terminal RS232 2xUSB 3.0 RJ-45 LAN HDMI UBOOT SIM TF DC
Ports - left panel:	-----
Ports - right panel:	-----
Power:	DC-12V
Supported OS:	Android 12/14
Installed OS:	Android 12/14
Dimensions:	305.9 x 211.2 x 51 mm
Weight:	2kg
Expansion:	2x speaker
Fanless:	Yes
Humidity:	5% - 95% Non-Condensing
Temp:	-10 °C to 60 °C
Storage Temp:	-20 °C to 70 °C
IP Norm:	-----
IP Level (back panel):	-----
IP Level (front panel):	IP65
Dual display:	Yes
Response time touch-panel (ms):	7-30 ms

Contrast Ratio:	800:1
Brightness:	300 cd/m2
Viewing Angle:	85/85/85/85(L/R/U/D)
Backlight MTBF:	Yes
Color Resolution:	16,7M
Surface hardness (display):	7H
Touch Life(contacts):	60000-70000
Housing material:	Aluminium
Mounting VESA:	75 x 75 mm 100 x 100 mm
Folding Bracket (for office type working):	Option
Power Consumption:	20-30 w
Others:	Color: Silver
Anti-vibration:	----
Anti-shock:	----
RFID scanner (reader):	LF (125 kHz) + HF (13,56 MHz - ISO14443A/B)
Barcode reader:	----

2 648,68 zł

net price: 2 153,40 zł

MOBITOUCH 116A-LF



SPECIFICATION AND PARAMETERS

DISPLAY AND TOUCH

RESISTANCE AND PROTECTION

COMMUNICATION AND CONNECTORS

APPLICATION

AVAILABLE VERSIONS AND ACCESSORIES



Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



Efficient cooling

The housing with notches used in the panel ensures good air exchange inside the device



Quick start

A modern eMMC drive will increase the speed of applications and programs and ensure quiet computer operation.



Efficient

The quad-core RK3568 improves the device's performance.



Bright Screen

The display with 300 cd/ m² brightness makes the picture much more vivid and better readable when used outside in the sun.



Wireless network

The panel can be connected to nearby wireless networks by equipping it with a Wi-Fi module



Resistive screen

The resistive screen allows precise handling and gentle on-screen movement.

Specifications and parameters

Performance

Processor	RK3568 (4x 2.0 GHz)
Graphics card	Integrated Intel HD Graphics
Operating system	Android 12
RAM	4GB
Drive	64GB eMMC
Display	
Screen	11.6" 1366x768
Touch screen	Resistive
Brightness	300cd/m ²
Screen ratio	16:9
View angle	85/85/85/85(L/R/U/D)
Interfaces	
Communication	WiFi Bluetooth
Connectors	Phoenix terminal RS232 USB 3.0 RJ-45 LAN HDMI UBOOT SIM TF DC
RFID	LF 125 kHz + HF 13,56 MHz
Other	
Dimensions	305.9 x 211.2 x 51 mm
Weight	2 kg
Casing material	Aluminium



Detailed device specification is available in the "Technical data".

The industrial PC panel uses an efficient and energy-saving RK3568 (4x 2.0 GHz) . In its interior there are four cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery".

NPU

A special type of chip designed to handle artificial intelligence tasks. It allows a device to recognize images, voice, or text more quickly, while also operating more efficiently and saving energy. The NPU enables the use of smart features without delays, which translates into a more convenient and modern everyday user experience.

Display and touch

Amplified, metal industrial computer Mobitouch 116A-LF has a water-resistant and scratch-proof 11.6" LED screen 1920x1080 resolution offers good image quality, and high brightness in the 300 cd/m² range gives better

color saturation and contrast and allows significantly improved visibility even in the case of incident light. The display of the resistive type provides the user with a clear image and ease of use by touch.

RESISTIVE SCREEN

A resistive screen is a type of touch screen that works by sensing pressure. It consists of several layers.

Resistance and protection

QUALITY OF MATERIALS

The panel PC has a good-quality metal casing. It is an important element of the cooling system thanks to specially designed cutouts that facilitate air circulation inside the housing. The overall design of the device is focused on simplicity and functionality, appreciated among professionals, as an accessory the panel can be equipped with passive cooling.



EXTREME TEMPERATURES

PanelPC Mobitouch 116A-LF is designed for continuous operation both at very low and high temperatures in the range from -10 ° C to 60 ° C. If the device is turned off, it can handle temperatures ranging from -20 ° C to 70 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 95% relative air humidity. It is also possible to purchase additional fanless cooling.

Work temp.	-10°C do 60°C
Storage temp.	-20°C do 70°C
Humidity	5% - 95% Non-Condensing

Communication and connectors

WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel Mobitouch 116A-LF has been equipped with standards -

802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

Standards	802.11a/b/g/n
Frequencies	2.4GHz



BLUETOOTH COMMUNICATION

Bluetooth enables short-range wireless communication between various electronic devices, such as keyboard computer, laptop, PDA, mobile phone and many others. In the fourth version of standard, energy consumption was significantly reduced transfer and the real range of operation was increased



CODE SCANNER (OPTION)

A barcode reader enables the scanning, decoding, and transferring of data stored in a

barcode to a computer. Thanks to dynamic scanning capabilities and a wide reading range, the data collector accurately captures information, helping to

improve work speed and efficiency. The entire system can be quickly set up, as the simplified installation process and intuitive, user-friendly design make getting the scanner ready for use very easy.

NFC

Near Field Communication, known as NFC, is a short-range wireless communication standard that allows for the wireless exchange of data over a distance of a few to several centimeters. This technology is a simple extension of the contactless card standard, combining the smart card interface and reader into a single device.


NFC devices can communicate both with existing ISO/IEC 14443 standard equipment (such as cards and readers), as well as with other NFC-enabled devices. This makes them compatible with existing and widely used public transport and payment infrastructures, such as MIFARE.




RFID READER

RFID is a technology used to identify objects and control the flow of products. Reading information

CONNECTORS AND INTERFACES



DIMENSIONS




Application



TRADE AND SERVICES

PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

WAREHOUSE AND MANAGEMENT



The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

TRANSPORT AND **MOTORIZATION**



Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

Available versions and accessories

Industrial Panel PC Mobitouch 116A-LF is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

	v.1	v.2	v.3	v.4	v.5	v.6	v.7	v.8	v.9
Screen beztouch		—	—	—	—	—	—	—	—
Capacitive screen	—					—	—	—	—
Screen rezystywny	—	—	—	—	—				
4GB RAM			—	—	—		—	—	—
8GB RAM	—	—				—			
64GB eMMC			—	—	—		—	—	—
128GB eMMC	—	—		—	—	—		—	—
256GB eMMC	—	—	—			—	—		
Scanner 2D EM23	—	—		—		—		—	
LF RFID 125kHz									