



MoTouch 12 v.1 - Industrial monitor with touch display - IP65 standard for front panels - with IP65 standard for the front part of the housing

Category:	Industrial touch screens
Manufacturer:	Mobilator
Ports - rear panel:	1x VGA, 1x HDMI, 1x DVI, 1x DC-IN, 1x RJ-45 (touch connector), 1x Audio I/O
Power:	12V~36V DC
Dimensions:	319mm x 257mm x 56.5mm
Weight:	2.5 kg
Expansion:	-----
Humidity:	to 95%
Temp:	-10°C ~ 60°C
Storage Temp:	-20°C ~ 70°C
IP Norm:	IP 65 on front
IP Level (back panel):	-----
IP Level (front panel):	IP 65
Screen size:	12"
Resolution:	1024x768
Aspect ratio:	4:3
Touchscreen:	Capacitive

Response time touch-panel (ms):	10 ms
Contrast Ratio:	1000:1
Brightness:	500 cd/m2
Viewing Angle:	85/85/85/85 (L/R/U/D)
Backlight MTBF:	TFT LCD
Color Resolution:	16.7M
Surface hardness (display):	-
Touch Life(contacts):	Infinity
Housing material:	rugged 3mm thickness aluminum
Mounting VESA:	Panel, Wall, Rack, Stand and Arm
Folding Bracket (for office type working):	No (optional)
Power Consumption:	18 W
Others:	-----
Anti-vibration:	-----
Anti-shock:	-----
Built-in speakers:	No

2 280,05 zł

net price: 1 853,70 zł

MoTouch 12



Menu

- Description
- Connector
- Screen
- Application
- Specifications



Industrial Touch Monitors

Small dimensions Industrial Panel Monitor are used in environments dominated by dust, dirt and moisture. They are ideal for applications requiring quiet and continuous operation. Industrial touch screen monitor, through its function of touch, replaces: mouse, keyboard, or other pointing device.

[go top...](#) [menu...](#)

Description





Mobilator	MoTouch 191	
		Resolution: 1024x768 / 4:3
		LCD size: 12"
		Backlight: TFT LCD
		Connectors:VGA/DVI/HDMI/Audio I/O
		Screen Protection: -
		Mounting: 75mm x 75mm / 100mm x 100mm
		Built-in speakers: -

	Detailed specification of the configuration available in the "Technical data"
--	--

Dimensions:

Housing dimension are **319 x 257 x 56.5 mm**. Housing is made of high quality aluminum what ensures a very high resistance to mechanical damages. This model with weight of only **2.5 kg** is ready at any time for operation even in extreme conditions such as heat, cold, vibration.





[go top...](#) [menu...](#)

Connector

For proper operation of the touch controller is needed connect the monitor to the computer using the USB cable.

Connector:

Touch monitor MoTouch 12 is equipped with the essential connectors such as:

1. RJ-45 (touch connector)	3. DVI	5. Audio I/O
2. HDMI	4. VGA	6. DC-IN



Screen

MoTouch 12 With 1024x768 resolution and high brightness of 500 cd/m2, screen of capacitive type with high sensitivity to touch, offers the user a clear picture and ease of use.

The LCD monitor has backlight TFT LCD. This technology allows for the construction and easy control of high-resolution displays, as well as obtaining much higher image quality.



Capacitive screen

Operation of this type of screen is a bit more complex than the resistive screens, but the comfort of their use is much higher. In the corners of the screen capacitive electrodes are placed emitting weak electric field. If you touch the display, the intensity produced before the field changes, and the system will calculate respectively, where the disturbance occurred.



Screen capacitive

