



MoTouch 8 - Industrial Monitor with IP65 on front cover

Category:	Industrial touch screens
Manufacturer:	Mobilator
Ports - rear panel:	1x VGA, 1x HDMI, 1x DVI, 1x DC-IN, 1x RJ-45 (touch connector);
Power:	12V DC
Dimensions:	223 x 183 x 43 mm
Weight:	5 kg
Expansion:	-----
Humidity:	10%~ 80%
Temp:	-20°C ~ 60°C
Storage Temp:	-20°C ~ 65°C
IP Norm:	IP 65 on front
IP Level (back panel):	-----
IP Level (front panel):	IP 65
Screen size:	8"
Resolution:	800 x 480 or 1024x768

Aspect ratio:	4:3
Touchscreen:	Capacitive
Contrast Ratio:	1000:1
Brightness:	400 cd/m2
Viewing Angle:	89/89/89/89(Typ.)(CR>10)
Backlight MTBF:	WLED
Color Resolution:	16.7M
Surface hardness (display):	-
Touch Life(contacts):	>50,000,000 times in one location without failure
Housing material:	rugged 3mm thickness aluminum
Mounting VESA:	Panel, Wall, Rack, Stand and Arm
Folding Bracket (for office type working):	No (optional)
Power Consumption:	60 W
Others:	-----
Anti-vibration:	-----
Anti-shock:	-----
Built-in speakers:	No

327,89 €
net price: 266,58 €

MoTouch 8



Menu

Description

Connector

Screen

Application

Specifications

Industrial Touch Monitors

Small dimensions Industrial Panel Monitor are used in environments dominated by dust, dirt and moisture. They are ideal for applications requiring quiet and continuous operation. Industrial touch screen monitor, through its function of touch, replaces: mouse, keyboard, or other pointing device.

[go top...](#)



Mobilator


MoTouch 8



Resolution: 800x600 or 1024x768 / 4:3



LCD size: 8"



Backlight: LED



Connectors: VGA/DVI/HDMI



Screen

Protection: -



Mounting:

75mm x

75mm /

100mm x

100mm



Built-in


speakers: -

Detailed specification
of the configuration
available in the
"Technical data"

Dimensions:

Housing dimension a
mechanical damages

heat, cold, vibration.



high resistance to
conditions such as

[go top...](#)

Connector

For proper operation of the touch controller is needed connect the monitor to the computer using the USB cable.

Connector:

Touch monitor MoTouch 8 is equipped with the essential connectors such as:

- | | |
|----------------------------|--------|
| 1. DC-IN 12-24V | 3. VGA |
| 2. HDMI | 4. DVI |
| 5. RJ-45 (touch connector) | |



Screen

MoTouch 8 With 800x480 or 1024x768 resolution and high brightness of 400 cd/m2, screen of capacitive type with high sensitivity to touch, offers the user a clear picture and ease of use.

The LCD monitor backlight LED technology results in realistic color rendering, energy consumption reduced by up to 40% and much lower failure rate compared to traditional LCD monitors with CCFL backlight.



Capacitive screen

Operation of this type of screen is a bit more complex than the resistive screens, but the comfort of their use is much higher. In the corners of the screen capacitive electrodes are placed emitting weak electric field. If you touch the display, the intensity produced before the field changes, and the system will calculate respectively, where the disturbance occurred.



Screen capacitive

