



Reinforced Capacitive Industrial Panel PC MobiBOX IP65 i7 21.5 Full HD v.3.1

Category:	Industrial Panel PC Computers
Manufacturer:	Mobikator
Supported OS:	Windows 7/8.1/10 Linux
Installed OS:	-----
Screen size:	21.5"
Resolution:	1920 x 1080
Aspect ratio:	16:9
Brightness:	400 cd/m2
Touchscreen:	Capacitive
CPU Support:	Intel Core i3/i5/i7
Installed CPU:	Intel Core i7 4510U (2x2.0GHz)
Graphic Card:	Intel HD Graphics
Storage (HDD) Support:	64GB/128GB/256 SSD
Installed Storage (HDD):	64GB SSD
Memory Support:	up to 4GB DDR3
Installed Memory:	4GB
IP Norm:	IP65 (przedni panel)
IP Level (front panel):	IP65

IP Level (back panel):	-----
Temp:	-10°C ~ 60°C
Storage Temp:	-30°C ~ 60°C
Humidity:	10%~ 90%
Anti-shock:	-----
Anti-vibration:	-----
Barcode reader:	-----
RFID scanner (reader):	-----
Others:	Housing color: Black or Silver
LAN:	Realtek RTL811E
Wireless LAN card:	Yes
3G:	No
Bluetooth:	No
GPS:	No
Ports - rear panel:	1x HDMI1x RS-2324x USB 2.01x VGA1x LAN1x DC-in
Ports - front panel:	-----
Ports - left panel:	-----
Ports - right panel:	-----
Expansion:	-----
Power:	12V DC-in
Power Consumption:	-----
Watch Dog Timer:	-----
Mounting VESA:	Yes
Folding Bracket (for office type working):	-----
Chipset:	Intel
CD/DVD Drive:	-----
Audio:	RTL ALC662
TV Tuner:	-----

Backlight MTBF:	LED
Contrast Ratio:	1000:1
Dual display:	Yes
Viewing Angle:	-----
Touch Life(contacts):	-----
Surface hardness (display):	-----
Color Resolution:	16.7 M
Response time touch-panel (ms):	5
Housing material:	Aluminum
Dimensions:	557mm x 345mm x 59.2mm
Fanless:	Yes
Weight:	5kg

6 180,75 zł

net price: 5 025,00 zł



SPECIFICATION AND PARAMETERS

DISPLAY AND TOUCH

RESISTANCE AND PROTECTION

COMMUNICATION AND CONNECTORS

APPLICATION

AVAILABLE VERSIONS AND ACCESSORIES

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



Waterproof

The IPX5 water-resistance standard on the front panel guarantees protection of the device for contact with water.



Dustproof

The dustproof IP6X standard on the front panel protects the panel against dust and access to hazardous parts.



Efficient

The dual-core Intel Core i7 processor supported by 4GB of RAM improves the device's performance.



Bright Screen

The display with 400cd/ m² brightness makes the picture much more vivid and better readable when used outside in the sun.



Wireless network



Capacitive screen

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module.

The capacitive screen allows precise handling and gentle on-screen movement.

Specifications and parameters

Performance	
Processor	Intel Core i7 4510U (2x 2.0GHz)
Graphics card	Intel HD Graphics
Operating system	Windows 7/8/10 Linux
RAM	4GB DDR3
Drive	64GB SSD
Display	
Screen	21.5" (1920x1080)
Touch screen	Capacitive
Brightness	400cd/m ²
Contrast	1000:1
Response time	5ms
Hardness	—

Interfaces	
Communication	Wi-Fi / 3G
Connectors	HDMI / VGA / RJ45 / 4x USB 2.0 / RS232 / Audio / DC 12V
Memory card	—
SIM card	—
Other	
Protection	IP65 (front panel)
Dimensions	557mm x 345mm x 59.2mm
Weight	5kg



Detailed device specification is available in the "Technical data" tab.

The dust-proof industrial PC panel uses an efficient and energy-saving Intel Core i7 4510U processor. In its interior there are two cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery" tab.

Display and touch

Amplified, waterproof industrial computer MobiBOX IP65 4510U 21.5 has a water-resistant and scratch-proof 21.5" LED screen 1920x1080 resolution offers good image quality, and high brightness in the 400 cd/m² range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident.

CAPACITIVE SCREEN

In the capacitive screen, the reaction of the device is not to directly press the screen, but to change the electrostatic field at the point where the device is touched.

This allows for much more precise handling and gentle brushes on the screen.

In addition, we can use multitouch technology, the ability to control our screen with a few fingers at once.



Resistance and protection

PROTECTION STANDARD **IP65**

IP norm (International Protection Rating) determines the degree of protection provided by the housing of an electrical device against such factors as: access to dangerous parts inside the housing, penetration of foreign solids and

splashing or immersion. The first characteristic number means that the housing protects people against access to dangerous parts located inside the device, and at the same time provides protection against penetration of foreign solids. The second characteristic digit means that the housing provides protection against the effects of water penetration.

IP6X (front panel)	Protection against access to dangerous parts with wire. Dustproof protection.
IPX5 (front panel)	Water projected by a nozzle (6.3 mm) against enclosure from any direction shall have no harmful effects.



EXTREME TEMPERATURES

PanelPC MobiBOX IP65 4510U 21.5 is adapted for continuous operation in both very low and high temperatures in the range from -10 ° C to 60 ° C. If the

device is switched off, it can already handle temperatures between -30 ° C and 60 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 90% relative humidity.

Work temp.	-10°C to 60°C
Storage temp.	-30°C to 60°C
Humidity	10% - 90%

Communication and connectors

WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel MobiBOX IP65 4510U 21.5 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

Standards	802.11a/b/g/n
Frequencies	2.4GHz 5GHz

CONNECTORS AND INTERFACES



Application

TRADE AND SERVICES

Waterproof and dustproof PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

WAREHOUSE AND MANAGEMENT

The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

TRANSPORT AND **M**OTORIZATION

Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

Available versions

Industrial industrial computer MobiBOX IP65 4510U 21.5 is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

	v.1	v.2	v.3	v.4	v.5	v.6	v.7
WiFi	+	+	+	+	+	+	+
3G	—	—	+	—	+	—	+

2GB RAM	+	-	-	-	-	-	-
4GB RAM	-	+	+	+	+	+	+
8GB RAM	-	-	-	-	-	-	-
64GB SSD	+	+	+	-	-	-	-
128GB SSD	-	-	-	+	+	+	-
256GB SSD	-	-	-	-	-	-	+
Dotyk rezystancyjny/Touch resistive	+	+	+	+	+	+	+
Dotyk pojemnościowy/Touch capacitive	-	-	-	-	-	-	-
	v.8	v.2.1	v.2.2	v.3.1	v.6.1	v.8.1	
WiFi	+	+	+	+	+	+	
3G	-	-	-	+	-	-	
2GB RAM	-	-	-	-	-	-	
4GB RAM	-	+	+	+	+	-	
8GB RAM	+	-	-	-	-	+	
64GB SSD	-	+	+	+	-	-	
128GB SSD	-	-	-	-	-	-	
256GB SSD	+	-	-	-	+	+	
Dotyk rezystancyjny/Touch resistive	+	+	-	-	-	-	
Dotyk pojemnościowy/Touch capacitive	-	-	+	+	+	+	