



Reinforced Capacitive Industrial Panel PC  
with thermal printer 80mm and reader  
RFID HF - MobiBOX J1900 15

<b>Category:</b>	Industrial Panel PC Computers
<b>Manufacturer:</b>	Mobilator
<b>Screen size:</b>	15"
<b>Resolution:</b>	1024 x 768
<b>Aspect ratio:</b>	4:3
<b>Touchscreen:</b>	Capacitive
<b>Chipset:</b>	Intel NM10 High Speed Chipset
<b>CPU Support:</b>	Intel Celeron J1900
<b>Installed CPU:</b>	Intel Celeron J1900 (4x2.0GHz)
<b>Memory Support:</b>	up to 4GB
<b>Installed Memory:</b>	4GB
<b>Graphic Card:</b>	Intel HD Graphics
<b>Audio:</b>	-----
<b>Storage (HDD) Support:</b>	32GB/64GB/128GB SSD
<b>Installed Storage (HDD):</b>	64GB SSD

<b>CD/DVD Drive:</b>	-----
<b>Wireless LAN card:</b>	Yes
<b>Bluetooth:</b>	Yes
<b>3G:</b>	No
<b>GPS:</b>	No
<b>TV Tuner:</b>	-----
<b>Watch Dog Timer:</b>	-----
<b>Ports - front panel:</b>	-----
<b>Ports - rear panel:</b>	1x HDMI1x RS-2324x USB 2.01x VGA1x LAN1x DC-in
<b>Ports - left panel:</b>	-----
<b>Ports - right panel:</b>	-----
<b>Power:</b>	12V DC-in
<b>Supported OS:</b>	Microsoft Windows
<b>Installed OS:</b>	Windows 7/8/10
<b>Dimensions:</b>	557mm x 345mm x 59.2mm
<b>Weight:</b>	5kg
<b>Expansion:</b>	-----
<b>Fanless:</b>	Yes
<b>Humidity:</b>	10%~ 90%
<b>Temp:</b>	-10°C ~ 60°C
<b>Storage Temp:</b>	-30°C ~ 60°C
<b>IP Norm:</b>	IP65 (przedni panel)
<b>IP Level (back panel):</b>	-----
<b>IP Level (front panel):</b>	IP65
<b>Dual display:</b>	Yes
<b>Response time touch-panel (ms):</b>	5
<b>Contrast Ratio:</b>	1000:1
<b>Brightness:</b>	350 cd/m2

<b>Viewing Angle:</b>	-----
<b>Backlight MTBF:</b>	LED
<b>Color Resolution:</b>	16.7 M
<b>Surface hardness (display):</b>	-----
<b>Touch Life(contacts):</b>	-----
<b>Housing material:</b>	Aluminum
<b>Mounting VESA:</b>	Yes
<b>Folding Bracket (for office type working):</b>	-----
<b>Power Consumption:</b>	-----
<b>Others:</b>	Housing color: Black or Silver
<b>Anti-vibration:</b>	-----
<b>Anti-shock:</b>	-----
<b>RFID scanner (reader):</b>	Yes, HF 13.56 MHz
<b>Barcode reader:</b>	-----

**Product from the Archive - production finished**



## Specification and parameters

## Display and touch

## Resistance and protection

## Communication and connectors

## Application

## Available versions

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



### Waterproof

The IPX5 water-resistance standard on the front panel guarantees protection of the device for contact with water.



### Dustproof

The dustproof IP6X standard on the front panel protects the panel against dust and access to hazardous parts.



### Efficient



### Bright Screen

The quad-core Intel Celeron processor supported by 4GB of RAM improves the device's performance.

The display with 350cd/ m<sup>2</sup> brightness makes the picture much more vivid and better readable when used outside in the sun.



### Wireless network

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module.



### Capacitive screen

The capacitive screen allows precise handling and gentle on-screen movement.

## Specifications and parameters

Performance	
Processor	Intel Celeron J1900 (4x 2.0GHz)
Graphics card	Intel HD
Operating system	Windows /7/8/10
RAM	4GB
Drive	64GB SSD
Display	

Screen	15" (1024x768)
Touch screen	Capacitive
Brightness	350cd/m <sup>2</sup>
Contrast	1000:1
Response time	5ms
Hardness	—
<b>Interfaces</b>	
Communication	Wi-Fi
Connectors	HDMI / VGA / RJ45 / 4x USB 2.0 / 2x COM RS232 / Audio / DC 12V / RFID
Method print	Thermal
Print width	58 mm or 80 mm
<b>Other</b>	
Protection	IP65 (front panel)
Dimensions	557mm x 345mm x 59.2mm
Weight	5kg



Detailed device specification is available in the "Technical data" tab.

The dust-proof industrial PC panel uses an efficient and energy-saving Intel Celeron J1900 processor. In its interior there are four cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically

allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery" tab.

## Display and touch

Amplified, waterproof industrial computer MobiBOX IP65 J1900 RFID HF 15 has a water-resistant and scratch-proof 15" LED screen 1024x768 resolution offers good image quality, and high brightness in the 350 cd/m<sup>2</sup> range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident.

## CAPACITIVE SCREEN

In the capacitive screen, the reaction of the device is not to directly press the screen, but to change the electrostatic field at the point where the device is touched.

This allows for much more precise handling and gentle brushes on the screen.

In addition, we can use multitouch technology, the ability to control our screen with a few fingers at once.



Resistance and protection

## PROTECTION STANDARD **IP65**

IP norm (International Protection Rating) determines the degree of protection provided by the housing of an electrical device against such factors as: access to dangerous parts inside the housing, penetration of foreign solids and splashing or immersion. The first characteristic number means that the housing protects people against access to dangerous parts located inside the device, and at the same time provides protection against penetration of foreign solids. The second characteristic digit means that the housing provides protection against the effects of water penetration.

IP6X (front panel)	Protection against access to dangerous parts with wire. Dustproof protection.
IPX5 (front panel)	Water projected by a nozzle (6.3 mm) against enclosure from any direction shall have no harmful effects.



## EXTREME TEMPERATURES

PanelPC MobiBOX IP65 J1900 RFID HF 15 is adapted for continuous operation in both very low and high temperatures in the range from -10 ° C to 60 ° C. If the device is switched off, it can already handle temperatures between -30 ° C and 60 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 90% relative humidity.

Work temp.	-10°C to 60°C
Storage temp.	-30°C to 60°C
Humidity	10% - 90%

## Communication and connectors

### WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel MobiBOX J1900 IP65 RFID HF 15 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

Standards	802.11a/b/g/n
Frequencies	2.4GHz   5GHz

### CONNECTORS AND INTERFACES



## Application

### TRADE AND SERVICES

Waterproof and dustproof PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

### WAREHOUSE AND MANAGEMENT

The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

## **TRANSPORT AND MOTORIZATION**

Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.