



Reinforced Resistant Industrial Panel PC MobiBOX IP65 i3 15.6 v.8

| | |
|---------------------------------|---------------------------------|
| Category: | Industrial Panel PC Computers |
| Manufacturer: | Mobikator |
| Supported OS: | Windows 7/8.1/10 Linux |
| Installed OS: | ----- |
| Screen size: | 15.6" |
| Resolution: | 1366x768 |
| Aspect ratio: | 16:10 |
| Brightness: | 400 cd/m2 |
| Touchscreen: | Resistive |
| CPU Support: | Intel Core i3/i5/i7 |
| Installed CPU: | Intel Core i3 4010U (2x 1.7GHz) |
| Graphic Card: | Intel HD Graphics 4400 |
| Storage (HDD) Support: | 32GB/64GB/128GB/256GB SSD |
| Installed Storage (HDD): | 256GB SSD |
| Memory Support: | up to 8GB DDR3 |
| Installed Memory: | 8GB |
| IP Norm: | IP65 (przedni panel) |
| IP Level (front panel): | IP65 |

| | |
|---------------------------------------------------|------------------------------------------------|
| IP Level (back panel): | ----- |
| Temp: | -10°C ~ 60°C |
| Storage Temp: | -30°C ~ 60°C |
| Humidity: | 10%~ 90% |
| Anti-shock: | ----- |
| Anti-vibration: | ----- |
| Barcode reader: | ----- |
| RFID scanner (reader): | ----- |
| Others: | Housing color: Black or Silver |
| LAN: | Realtek RTL811E |
| Wireless LAN card: | Yes |
| 3G: | No (available in other configuration) |
| Bluetooth: | No |
| GPS: | No |
| Ports - rear panel: | 1x HDMI1x RS-2324x USB 2.01x VGA1x LAN1x DC-in |
| Ports - front panel: | ----- |
| Ports - left panel: | ----- |
| Ports - right panel: | ----- |
| Expansion: | ----- |
| Power: | 12V DC-in |
| Power Consumption: | ----- |
| Watch Dog Timer: | ----- |
| Mounting VESA: | Yes |
| Folding Bracket (for office type working): | ----- |
| Chipset: | Intel |
| CD/DVD Drive: | ----- |
| Audio: | RTL ALC662 |
| TV Tuner: | ----- |

| | |
|----------------------------------------|----------------------|
| Backlight MTBF: | LED |
| Contrast Ratio: | 1000:1 |
| Dual display: | Yes |
| Viewing Angle: | ----- |
| Touch Life(contacts): | ----- |
| Surface hardness (display): | ----- |
| Color Resolution: | 16.7 M |
| Response time touch-panel (ms): | 5 |
| Housing material: | Aluminum |
| Dimensions: | 420mm x 269mm x 57mm |
| Fanless: | Yes |
| Weight: | 3kg |

Product from the Archive - production finished



SPECIFICATION AND PARAMETRS

DISPLAY AND TOUCH

RESISTANCE AND PROTECTION

COMMUNICATION AND CONNECTORS

APPLICATION


AVAILABLE VERSIONS AND ACCESSORIES

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



Waterproof

The IPX5 water-resistance standard on the front panel guarantees protection of the device for contact with water.



Dustproof

The dustproof IP6X standard on the front panel protects the panel against dust and access to hazardous parts.



Efficient

The dual-core Intel Core i3 processor supported by 8GB of RAM improves the device's performance.



Bright Screen

The display with 400/ m² brightness makes the picture much more vivid and better readable when used outside in the sun.



Wireless network

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module.



Resistive screen

The resistive screen allows you to freely use the touch screen of the PC panel in gloves or with a stylus.



Specifications and parameters

| Performance | |
|------------------|----------------------------------|
| Processor | Intel Core i3-4010U (2x 1.70GHz) |
| Graphics card | Intel HD Graphics 4400 |
| Operating system | Windows 7/8/10 Linux |
| RAM | 8GB DDR3 |
| Drive | 256GB SSD |
| Display | |

| Screen | 15.6" (1366x768) |
|---------------|---------------------------------------------------------|
| Touch screen | Resistive |
| Brightness | 400cd/m ² |
| Contrast | 1000:1 |
| Response time | 5ms |
| Hardness | — |
| Interfaces | |
| Communication | Wi-Fi |
| Connectors | HDMI / VGA / RJ45 / 4x USB 2.0 / RS232 / Audio / DC 12V |
| Memory card | — |
| SIM card | — |
| Other | |
| Protection | IP65 (front panel) |
| Dimensions | 420mm x 269mm x 57mm |
| Weight | 3kg |



Detailed device specification is available in the "Technical data" tab.

The dust-proof industrial PC panel uses an efficient and energy-saving Intel Core i3-4010U processor. In its interior there are two cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the

average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.



More photos in full resolution available in the "Gallery" tab.

Display and touch

Amplified, waterproof industrial computer MobiBOX IP65 4010U 15.6 has a water-resistant and scratch-proof 15.6" LED screen 1366x768 resolution offers good image quality, and high brightness in the 400 cd/m² range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident The display of the resistive type provides the user with a clear image and ease of use by touch.

RESISTIVE SCREEN

In the resistive screen, the sensitive surface is made of two plastic plates. The plate on the surface is made of thin and scratch-resistant plastic. It is also covered with a thin layer of conductive materials placed on the bottom of the screen. Under the top glass (i.e. below the conductive material) is a second plastic plate. Both tiles have no contact with each other until the user of the device has pressed the screen with a finger or stylus. Then there is contact between slightly separated screens. As a result of their contact, a short-circuit is created, which by measuring the vertical and horizontal resistance is converted into data indicating the processor's contact point.



Resistance and protection

PROTECTION STANDARD IP65

IP norm (International Protection Rating) determines the degree of protection provided by the housing of an electrical device against such factors as: access to dangerous parts inside the housing, penetration of foreign solids and splashing or immersion. The first characteristic number means that the housing protects people against access to dangerous parts located inside the device, and at the same time provides protection against penetration of foreign solids. The second characteristic digit means that the housing provides protection against the effects of water penetration.

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------|
| IP6X (front panel) | Protection against access to dangerous parts with wire. Dustproof protection. |
| IPX5 (front panel) | Water projected by a nozzle (6.3 mm) against enclosure from any direction shall have no harmful effects. |



EXTREME TEMPERATURES

PanelPC MobiBOX IP65 4010U 15.6 is adapted for continuous operation in both very low and high temperatures in the range from -10 ° C to 60 ° C. If the device is switched off, it can already handle temperatures between -30 ° C and 60 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 90% relative humidity.

| | |
|----------------------|---------------|
| Work temp. | -10°C to 60°C |
| Storage temp. | -30°C to 60°C |
| Humidity | 10% - 90% |

Communication and connectors

WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel MobiBOX IP65 4010U 15.6 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

| | |
|-------------|---------------|
| Standards | 802.11a/b/g/n |
| Frequencies | 2.4GHz 5GHz |

CONNECTORS AND INTERFACES



Application

TRADE AND SERVICES

Waterproof and dustproof PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the

VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

WAREHOUSE AND MANAGEMENT

The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

TRANSPORT AND MOTORIZATION

Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

Available versions and accessories

Industrial industrial computer MobiBOX IP65 4010U 15.6 is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the

parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

| | v.1 | v.2 | v.3 | v.4 | v.5 | v.6 |
|----------------------------------|-----|-----|-------|-------|-------|-------|
| WiFi | + | + | + | + | + | + |
| 3G | - | - | + | - | + | - |
| 2GB RAM | + | - | - | - | - | - |
| 4GB RAM | - | + | + | + | + | + |
| 8GB RAM | - | - | - | - | - | - |
| 32 GB SSD | + | - | - | - | - | - |
| 64 GB SSD | - | + | + | - | - | - |
| 128 GB SSD | - | - | - | + | + | - |
| 256 GB SSD | - | - | - | - | - | + |
| Dotyk rezystywny / Resistive | + | + | + | + | + | + |
| Dotyk pojemnościowy / Capacitive | - | - | - | - | - | - |
| | v.7 | v.8 | v.2.1 | v.4.1 | v.6.1 | v.8.1 |
| WiFi | + | + | + | + | + | + |
| 3G | + | - | - | - | - | - |
| 2GB RAM | - | - | - | - | - | - |
| 4GB RAM | + | - | + | + | + | - |
| 8GB RAM | - | + | - | - | - | + |
| 32 GB SSD | - | - | - | - | - | - |
| 64 GB SSD | - | - | + | - | - | - |
| 128 GB SSD | - | - | - | + | - | - |
| 256 GB SSD | + | + | - | - | + | + |
| Dotyk rezystywny / Resistive | + | + | - | - | - | - |
| Dotyk pojemnościowy / Capacitive | - | - | + | + | + | + |