



Reinforced Resistant Industrial Panel PC QBox 08H v.1

Category:	Industrial Panel PC Computers
Manufacturer:	Mobilator
Screen size:	8.4"
Resolution:	800 x 600
Aspect ratio:	-----
Touchscreen:	Resistive
Chipset:	-----
CPU Support:	Intel® Celeron® N2807 (2x 1.58GHz)
Installed CPU:	Intel® Celeron® N2807 (2x 1.58GHz)
Memory Support:	up to 4GB DDR3
Installed Memory:	2GB
Graphic Card:	Intel GMA 3600
Audio:	RTL ALC662
Storage (HDD) Support:	32GB/64GB SSD
Installed Storage (HDD):	32GB SSD
CD/DVD Drive:	-----
LAN:	Yes
Wireless LAN card:	No (available in other configuration)

Bluetooth:	No
3G:	No
GPS:	No
TV Tuner:	----
Watch Dog Timer:	----
Ports - front panel:	1x RS-2323x USB 2.01x USB 3.01x VGA1x LAN1x DC-in
Ports - rear panel:	----
Ports - left panel:	----
Ports - right panel:	----
Power:	12V DC-in
Supported OS:	Windows 7/8.1/10/CE Linux
Installed OS:	----
Dimensions:	235 x 185 x 55mm
Weight:	2kg
Expansion:	Uchwył VESA
Fanless:	Yes
Humidity:	10%~ 95%
Temp:	0°C ~ 60°C
Storage Temp:	-20°C ~ 80°C
IP Norm:	IP65 (front panel)
IP Level (back panel):	----
IP Level (front panel):	IP65
Dual display:	Nie
Contrast Ratio:	600:1
Brightness:	450 cd/m2
Viewing Angle:	80/80/80/60
Backlight MTBF:	LED
Color Resolution:	16.2 M

Surface hardness (display):	3H
Touch Life(contacts):	-----
Housing material:	Aluminum Alloy
Mounting VESA:	Yes
Folding Bracket (for office type working):	-----
Power Consumption:	-----
Others:	Housing color: Black
Anti-vibration:	-----
Anti-shock:	-----
RFID scanner (reader):	-----
Barcode reader:	-----

Product from the Archive - production finished



Specification and parameters

Display and touch

Resistance and protection

Communication and connectors

Application


Available versions and accessories

Industrial PC panels are integrated devices consisting of a PC computer and a touch monitor. Due to their design, they can work even under severe conditions prevailing in industrial environments, such as high humidity, high dustiness, contact with water or very low or high temperatures. These panels are characterized by high efficiency and stability of operation in all conditions.



Wodoodporny

The IPX5 water-resistance standard on the front panel guarantees protection of the device for contact with water.



Dustproof

The dustproof IP6X standard on the front panel protects the panel against dust and access to hazardous parts.



Efficient

The dual-core Intel Atom processor supported by



Bright Screen

2GB of RAM provides improved device performance.

The display with 450cd/ m² brightness makes the picture much more vivid and better readable when used outside in the sun.



Wireless network

The panel can be connected to nearby wireless networks by equipping it with an optional Wi-Fi module.



Resistive screen

The resistive screen allows you to freely use the touch screen of the PC panel in gloves or with a stylus.

Specifications and parameters

Performance	
Processor	Intel Celeron N2807 (2x 1.58GHz)
Graphics card	Intel GMA 3600

Performance	
Operating system	Windows 7/8/10/CE Linux
RAM	2GB/4GB * DDR3
Drive	32GB/64GB * SSD
Display	
Screen	8.4" (800x600)
Touch screen	Resistive
Brightness	450cd/m ²
Contrast	600:1
View angle	80/80/80/60
Hardness	3H
Interfejsy	
Communication	Wi-Fi *
Connectors	VGA RJ45 3x USB 2.0 1x USB 3.0 RS232 DC 12V
Memory card	No
SIM card	No
Inne	
Protection	IP65 (front panel)
Dimensions	235mm x 185mm x 55mm
Weight	2kg

* Optional equipment, available only in specific versions of the device.



Detailed device specification is available in the "Technical data" tab.

The dust-proof industrial PC panel uses an efficient and energy-saving Intel Atom N2800 processor. In its interior there are eight cooperating cores enabling more efficient processing of many tasks at the same time. Shared cache memory in which a multi-level hierarchy is used is dynamically allocated to each processor core depending on the load. This reduces the average access time to the main memory. Improved graphics card technology allows you to enjoy movies at full resolution and HD quality.





More photos in full resolution available in the "Gallery" tab.

Display and touch

Amplified, waterproof industrial computer QBox 08 has a water-resistant and scratch-proof 8.4" LED screen 800x600 resolution offers good image quality, and high brightness in the 450 cd / m² range gives better color saturation and contrast and allows significantly improved visibility even in the case of incident light. The display of the resistive type provides the user with a clear image and ease of use by touch.

RESISTIVE SCREEN

In the resistive screen, the sensitive surface is made of two plastic plates. The plate on the surface is made of thin and scratch-resistant plastic. It is also covered with a thin layer of conductive materials placed on the bottom of the screen. Under the top glass (i.e. below the conductive material) is a second plastic plate. Both plates have no contact with each other until the user of the device has pressed the screen with a finger or stylus. Then there is contact between slightly separated screens. As a result of their contact, a short-circuit is created, which by measuring the vertical and horizontal resistance is converted into data indicating the processor's contact point.

PROTECTION STANDARD **IP65**

IP norm (International Protection Rating) determines the degree of protection provided by the housing of an electrical device against such factors as: access to dangerous parts inside the housing, penetration of foreign solids and splashing or immersion. The first characteristic number means that the housing protects people against access to dangerous parts located inside the device, and at the same time provides protection against penetration of foreign solids. The second characteristic digit means that the housing provides protection against the effects of water penetration.

IP6X (front panel)	Protection against access to dangerous parts with wire. Dustproof protection.
IPX5 (front panel)	Protection against water jets (12.5 l / min) poured onto the housing from any side.

EXTREME **TEMPERATURES**

PanelPC QBox 08 is adapted for continuous operation in both very low and high temperatures in the range from 0 ° C to 60 ° C. If the device is switched off, it can already handle temperatures between -20 ° C and 80 ° C. In addition, the durable PanelPC is perfect for rooms with increased humidity, ensuring proper functioning even in the case of 95% relative humidity.

Work temp.	0°C do 60°C
Storage temp.	-20°C do 80°C
Humidity	10% - 95%

Komunikacja i złącza


Optional equipment

WIRELESS WI-FI NETWORK

The dual-band Wi-Fi module provides quick access to the network wherever you can connect to secured or open Wi-Fi networks. This is a convenient solution for people who have a router at home or place of residence and a wireless network that can be used at no extra charge. The shockproof industrial panel QBox 08 has been equipped with standards - 802.11n, which allows transfer of files at a dizzying speed of up to 150 Mb/s.

Standards	802.11a/b/g/n
Frequencies	2.4GHz 5GHz

CONNECTORS AND INTERFACES



Application

TRADE AND SERVICES

Waterproof and dustproof PC Panel is widely used primarily in the commercial industry, for example for controlling the sales system, displaying product information on monitors or advertising on large screens. With the VESA holder in the housing there are many possibilities for its assembly, eg in stores (at the cash register) in factory halls, in a car delivering products, etc. It will certainly be used in all types of retail chains.

WAREHOUSE AND MANAGEMENT

The industrial panel computer thanks to the RS232 interface can be used to connect many devices in the warehouse and facilitate their control. And its rugged housing is ideally suited to the harsh conditions prevailing in such rooms. No dust or dirt will prevent him from working, he will work without complaints even in a large dusty and dirty environment.

TRANSPORT AND MOTORIZATION

Panel computers can be used in transport by adapting it to work on 12V power supply. Then Panel PC can be used in passenger cars, buses, trams, taxis, trains and even in airplanes. Thanks to the integrated monitor, these panels perform very well in vehicles where mobility and the small size of the device are important.

Available versions and accessories

Industrial industrial computer QBox 08 is offered in several versions adapted to different needs. By clicking on the number of the hardware configuration you will be redirected to the product with the parameters given in the table below. In addition, it is possible to create a configuration that is currently unavailable on the customer's request.

	v.1	v.2	v.3
4GB/64GB	—		
Module Wi-Fi	—	—	