



Skaner 1D

Rugged waterproof industrial data collector Emdoor I62H 1D Scanner



| | |
|-------------------------------------|--|
| Category: | UMPC - Ruggedized |
| Manufacturer: | EMDOOR |
| Operating System: | Windows 10 IoT Enterprise(optional) |
| Display: | 5.98" (1280x720 IPS) Gorilla Glass Capacitive (5-point) |
| Brightness: | 430Nit |
| Processor: | Intel Cherrytrail Z8350 1.44Ghz-1.92GHz |
| Memory: | 2GB DDR3L |
| Hard Drive: | ----- |
| Flash Memory: | Yes |
| Touch screen: | Yes |
| Durability: | IP67 |
| Drop: | 1.2 meters |
| Shock: | ----- |
| Vibration: | ----- |
| Temperature: | Operating Temperature: -20°C -- +60°C Storage temperature: -30°C -- +70°C |
| Humidity: | 95% (no condensation) |
| 1D barcode scanner (reader): | 1D Honeywell N4313 |

| | |
|--|---|
| 2D barcode scanner (reader): | lack(available in other version) |
| RFID scanner (reader): | lack(available in other version) |
| Other: | ----- |
| Battery: | 3.7V 5000mAH |
| Working time on battery: | ----- |
| Fast battery replacement ability: | Yes |
| HotSwap battery: | ----- |
| LAN: | No |
| WLAN: | Dual Band 802.11 a/b/g/n 2.4G + 5.8G |
| Bluetooth: | Bluetooth 4.1class 1.5 range up to 10m |
| WAN: | 3G WCDMA(900/2100MHz) GSM 900/1800MHz HSDPA 7.2Mbps HSUPA 5.1 |
| GPS: | Built-in |
| Camera: | Rear: 5Mpx, Front: 2Mpx |
| In/Out: | 1 x microUSB, 1 x AudioJack , 1 x Micro SD, 1 x SIM 1 x Docking |
| Optional accessories: | ----- |
| Docking station connector: | Yes |
| VESA standard – holders and mounts support: | ----- |
| COM port: | ----- |
| Magnetic card reader (MSR): | ----- |
| Microchip card reader: | ----- |
| Contrast: | ----- |
| Graphics card: | Intel HD Graphics 400 |
| Chipset: | ----- |
| BIOS: | ----- |
| Casing material: | ----- |
| Flash Card Reader: | microSD (max. 128GB) |
| CD/DVD: | ----- |
| Audio: | AudioJack : Built-in Speaker : Microphone |

| | |
|--|---------------------------|
| Keyboard: | On-screen + Function Keys |
| Additional Navigation Devices : | ----- |
| Color: | ----- |
| Swivel Hinge: | ----- |
| VGA out: | No |
| TV Out: | ----- |
| TV Tuner: | ----- |
| Security: | MIL-STD-810G |
| Waterproof: | IP67 |
| Sand and dust: | IP67 |
| Size: | 185 x 93 x 20.7mm - 380g |
| Fanless casing: | Yes |

Product from the Archive - production finished



Rugged waterproof industrial data collector Emdoor I62H has a specially designed, reinforced structure, adapted to harsh environmental conditions. Similarly, as the equipment produced for the military, meets the requirements of IP67 norm. Thanks to its structure is resistant to dust and water. The device is proper for use in the home and industry.



| | |
|-----------------------|---|
| Processor | Intel Cherrytrail Z8350 |
| GPU | Intel HD Graphics 400 |
| Display | 5.98" (1280x720 IPS) Gorilla Glass Capacitive (5-point) |
| RAM memory | 2GB DDR3L |
| ROM memory | 32GB |
| Connectors | Micro USB Micro SD SIM 3.5mm Jack Docking |
| GPS | GLONASS, QZSS, GPS |
| Audio | Speaker Microphone |
| Camera | 5Mpx Rear, 2Mpx Front |
| Battery | 3.7V/5000mAH |
| Keyboard | On-Screen + Function keys |
| Environment | Windows 10 IoT Enterprise(optional) |
| Modules(factory) | 3G GPS WiFi 802.11 a/b/g/n Bluetooth 4.1 |
| Modules(optional) | NFC |
| Dimensions and weight | 185 x 93 x 20.7mm - 380g |
| Resistance | IP67 |
| Readers(factory) | 1D Honeywell |
| Readers(optional) | 2D Honeywell |
| Sensors | G-sensor Gyroscope E-compass Light indicator |

Barcode Scanner

Barcode Recognition
method and
and efficiency



Thanks to dynamic scanning
helps to increase the rate
the scanner work very easy

and quickly.

Near Field Communication (NFC)

Its a set of ideas and technology that enables smartphones and other devices to establish radio communication with each other by touching the devices together or bringing them into proximity to a distance of typically 10 cm or less.



| | NFC(optional) |
|-------------------------|-----------------|
| Frequency | 13.56 MHz |
| Reading distance | up to 4 cm |
| Supported card standard | Mifare |
| Supported standards | ISO/IEC 14443 A |
| | ISO/IEC 15693 |
| | ISO/IEC 18092 |

[go top...](#)





Applicable standards

| | |
|-----------|--------------------|
| Storage | -30°C -- +70°C |
| Operating | -20°C -- +60°C |
| Dust | IP6x (dust) |
| Water | IPx7 (water) |
| Drop | 1.2m |
| Humidity | 95% non-condensing |



IP67 Resistance

IP stands for Ingress Protection and is essentially a rating system developed by the International Electrotechnical Commission or IEC. The IP rating system is now being used to classify different degrees of protection against intrusion or immersion. The IP rating is usually followed by two digits. The first indicates the level of dust-resistance, the second water resistance. Dust-resistance levels goes from 0 up to 6 while water resistance goes from 0 to 8.

| | | | | |
|---|---|---|---|--|
| No special protection | 0 |  | 0 | No waterproofing |
| Protection from solid objects greater than 50mm in diameter | 1 |  | 1 | Protection from dripping water |
| Protection from solid objects greater than 50mm in diameter | 2 |  | 2 | Protection from vertically dripping water (tilted) |
| Protection from object not greater than 2,5mm in diameter | 3 |  | 3 | Protection from sprayed water (tilted up to 60°) |



When device is equipped with the **WCDMA** module, you need only insert a SIM card in the special slot and you are able instantly connect to the internet. Integrated software allows you to automatically detect and configure connections to mobile networks. Internal **3G** module Emdoor I62H adjusts automatically to transfer and network coverage.

| | |
|------------------|--|
| WiFi | Dualband 802.11(a/b/g/n) 2.4G+5.8G |
| GPS | GLONASS, QZSS, GPS |
| Bluetooth | Bluetooth V4.1 |
| 3G | WCDMA(900/2100MHz) GSM 900/1800MHz HSDPA 7.2Mbps HSUPA 5.76 |



You no longer need to worry about whether you will put your device into a briefcase, backpack or travel bag, the problem disappears when you have Emdoor I62H. The device weighs just 380g and its dimensions (185 x 93 x 20.7mm) allow you to take this device everywhere. Professional performance and energy efficiency makes, that Emdoor I62H is in a group of devices which enjoy great popularity in the market in the industrial segment.

Dimensions

185 x 93 x 20.7mm

Weight

380g

Quick change battery

Friendly design allows for fast replacement of the battery. This is useful when you working in the field with difficult conditions, where there is no additional power sources and the time is very important.



[go top...](#)

[more photos in the "Photo Gallery" ...](#)

[specification](#) of this version is available in the "Technical data" ...

product **does not have** any accesories in set...

| | v.1 | v.2 | v.3 | v.4 | v.5 | v.6 | v.7 | v.8 |
|----------------------------|-----|-----|-----|-----|-----|-----|-----|-----|
| NFC | - | + | - | - | + | - | + | + |
| Scanner 1D Honeywell N4313 | - | - | - | + | + | - | - | - |
| Scanner 2D Honeywell N3680 | - | - | - | - | - | + | + | + |
| Windows 10 Pro licence | - | - | + | - | - | - | - | + |